

CATALOG NUMBER	CONDUCTOR RANGE (MIN - MAX)	ACSR	AAAC	AAC	DIM A	DIM B	COLOR CODE	APPROX. WT. EACH LB. [KG]	STANDARD PACK
GL401	.184-.263 [4.68-6.70]	6 - 4	6 - 4	6 - 4	14 [230]	1.0 [25]	BLUE	0.431 [0.20]	25
GL402A	.225-.250 [5.59-6.35]	4	4	4	9 [230]	0.9 [23]	ORANGE	0.216 [0.10]	50
GL404A	.280-.320 [7.11-8.13]	2	2	2	12 [305]	1.0 [25]	RED	0.353 [0.16]	25
GL4042A	.220-.320 [5.59-8.13]	4 - 2	4 - 2	4 - 2	12 [305]	1.0 [25]	RED-ORANGE	0.266 [0.12]	25
GL406A	.355-.400 [9.02-10.16]	1/0	1/0	1/0	12 [305]	1.1 [28]	YELLOW	0.376 [0.17]	25
GL4076A	.355-.470 [9.02-11.94]	1/0 - 2/0	1/0 - 2/0	1/0 - 2/0	18 [460]	1.4 [36]	YELLOW-GRAY	1.058 [0.48]	25
GL407	.400-.470 [10.16-11.94]	2/0	2/0	2/0	18 [460]	1.4 [36]	GRAY	1.058 [0.48]	25
GL408	.450-.530 [11.43-13.46]	3/0	3/0	3/0	20 [510]	1.6 [41]	BLACK	1.588 [0.72]	25
GL4098	.450-.595 [11.43-15.11]	3/0 - 4/0	3/0 - 4/0	3/0 - 4/0	22 [560]	1.7 [43]	PINK-BLACK	1.953 [0.89]	25
GL409A	.505-.595 [12.83-15.11]	4/0	4/0	4/0	17 [430]	1.6 [41]	PINK	1.286 [0.58]	25
GL410	.603-.666 [15.32-16.92]	266.8 (18/1)	312.8	336.4	19 [480]	1.7 [43]	BROWN	1.411 [0.64]	25
GL411	.659-.724 [16.74-18.39]	336.4 (18/1)	394.5	397.5,336.4	20 [510]	1.8 [46]	GREEN	1.842 [0.83]	25
GL412	.720-.795 [18.29-20.19]	397.5 (17/1)	465.4	477	22 [560]	2.0 [51]	BLUE	2.352 [1.06]	25
GL413	.780-.858 [19.81-21.79]	477 (18/1)	559.5	556.5,500	24 [210]	2.1 [54]	WHITE	2.842 [1.29]	25

ITEM	DESCRIPTION	MATERIAL
1	CENTERSTOP	PLASTIC
2	SPRING	STAINLESS STEEL OR GALVANIZED STEEL
3	TUBING	ALUMINUM
4	JAW	ALUMINUM
5	NOSE GUIDE ASSEMBLY	STEEL
6	PILOT CUP	ALUMINUM
7	ID RING	PLASTIC

NOTES:

1. ALL DIMENSIONS FOR REFERENCE ONLY. DISTANCE IN. [MM], FORCE LBS. [kN], TORQUE IN. LBS. [N.m], & WEIGHT LBS. [KG].

2. RATINGS:

A. WILLHOLD A MINIMUM OF 95% OF THE GUY WIRE RATED BREAKING STRENGTH.

B. CLASS A CURRENT RATING PER ANSI C119.4.

75536	08/29/18	JT	SD
EC #	DATE	CHG BY	RESP ENG
DESC OF DWG: INITIAL RELEASE			
REASON (S) FOR CHANGE: DISPOSITION OF MAT'L:			

HPS

CONFIDENTIAL: THIS DRAWING AND ITS CONTACTS ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF HUBBELL POWER SYSTEMS. NO PUBLICATION, DISTRIBUTION OR COPIES MAY BE MADE WITHOUT THE WRITTEN CONSENT OF HUBBELL POWER SYSTEMS. HUBBELL POWER SYSTEMS UNPUBLISHED ALL RIGHTS RESERVED UNDER THE COPYRIGHT LAWS

HUBBELL®

POWER SYSTEMS, INC.

OVERHEAD LINE SPLICES
AUTOMATIC ALUMINUM

SIZE C	DWG NO. CC-25272	CAT / PART / ASSY NO. SEE TABLE	REV 00
-----------	---------------------	------------------------------------	-----------

DO NOT SCALE THIS DRAWING	DRN BY JT	DATE 12/22/17	SHEET 1 OF 1
---------------------------	--------------	------------------	-----------------